





Henkelman BV PO Box 2117 5202 CC 's-Hertogenbosch The Netherlands Tel +31 (0)73 - 621 36 71 Fax +31 (0)73 - 622 13 18 info@henkelman.com www.henkelman.com

Your distributor

'Pure Vacuum' STANDS FOR HENKELMAN CLEAR DESIGN **AND HIGH PERFORMANCE VACUUM PACKAGING TECHNOLOGY**

HENKELMAN, PURE VACUUM

Henkelman specialises in the development, production and distribution of state-of-the-art vacuum packaging machines. Our leading position in the field of vacuum technology sets us apart from the competition with the largest and most varied range of solutions for the vacuum packaging of food and other products. This is why companies in all types of sectors across the world choose the reliability of Henkelman.

Our machines are 'Made in Holland'. And you can tell. They combine a tightly crafted and functional design with optimum ease of operation and a long life span. Installation is just a matter of 'plug & pack', and the smart design ensures that hygiene standards are maintained at all times.

You can be sure that your machine will be delivered quickly, thanks to Henkelman's extensive international network of authorised dealers. This network guarantees a high-quality, personalised service and a rapid, efficient response to any questions you may have.

Henkelman, pure for an optimum packaging process...













SERIES









JUMBO PLUS





MINI IUMBO

- Capacity pump oo4 m³/h • Machine cycle 25-60 sec.
- Dimensions (l x w x h) • Dimensions (l x w x h) 450 X 330 X 295 mm
- Weight 25 kg
- Voltage 230V-1-50 Hz
- (other voltages available) • Power 0,30 kW • Power 0,40 kW





JUMBO PLUS

- Capacity pump oo8 m³/h
- Machine cycle 15-35 sec.
- 450 X 330 X 295 mm
- Weight 30 kg
- Voltage 230V-1-50 Hz (other voltages available)

JUMBO 35 IUMBO 30







JUMBO 30

Option H 130 mm (high lid)

- Machine cycle 20-40 sec.
- Dimensions (l x w x h) 525 X 450 X 370 mm
- Voltage 230V-1-50 Hz
 - Power 0,40 kW



- Capacity pump oo8 m³/h
- Weight 35 kg
- (other voltages available)



JUMBO 35

- Capacity pump o16 m³/h
- Machine cycle 15-30 sec. • Dimensions (l x w x h)
- Weight 48 kg
- Voltage 230V-1-50 Hz (other voltages available)
- Power 0,55 kW



- Machine cycle 20-40 sec. • Dimensions (l x w x h)

420 mm

• Capacity pump o16 m3/h

525 x 480 x 430 mm

• Voltage 230V-1-50 Hz

(other voltages available)

• Weight 56 kg

• Power 0,55 kW

JUMBO 42



JUMBO 42

JUMBO 42 XL









JUMBO 42XL

- Capacity pump o16 m3/h
- Machine cycle 20-45 sec.
- Dimensions (l x w x h) 610 x 480 x 470 mm
- Weight 67 kg
- Voltage 230V-1-50 Hz (other voltages available)
- Power 0,55 kW



- Dimensions (l x w x h) 570 x 480 x 610 mm
- Swivel castors lock & brake Extended mobility
- Labels and pouches storage
- Optimal use of space

JUMBO SERIES

FAST AND ROBUST VACUUMPACKAGING MACHINES WITH WORLD WIDE REPUTATION

- Compact system with "Jumbo" results
- Clear added value for company and product
- Modern table models with proven packaging achievements
- Professional vacuumpackaging for an attractive price
- Digital command and maintenance functions
- User friendly and low maintenance
- Easy to clean

FOOD PRODUCTS

Retail - Restaurants - Catering - Supermarkets (meat, poultry, fish, cheese, vegetables etc.)

- Longer shelf life (no contamination or bacteria's multiplication)
- Optimal product and storage hygiene (hermetically sealed)
- No loss of product (prevents drying out, moulds and freeze burn)
- Improved product quality (product maturing in packaging, no loss of aroma)
- Cost savings due to longer shelf life (larger purchasing orders, efficient cooking time spreading)
- Increased turnover due to longer shelf life (more variation and spread in product range)
- Professional product presentation
- Optimal packaging contributes to food safety and HACCP
- Ideal for cuisine-sous-vide applications

INDUSTRIAL PRODUCTS

Electronics - Semi-conductors - Metal - Pharmaceutical Products -Textiles - Laboratories - Automotive - etc.

- Moisture free packaging
- Air and dust free packaging
- Volume reducing packaging
- Scrapes and scratches free solution
- Fraud resistant packaging
- Sterile and contamination free packaging





GENERAL

- Table model
- Suitable for a large range of product and dimensions
- Full stainless steel conception
- Deep-drawn vacuum chamber with round corners for optimal hygiene
- Transparent lid
- Easily removable wireless sealing bars
- Insert plates for fast vacuum cycle and product adjustment
- Gentle air flow return for better product protection
- Compact budget

PACKAGING FUNCTIONS

Vacuum

Optimal final vacuum 99,80% (2 mbar)

SEALING FUNCTIONS

Double seal

2 x 3.5 mm convex sealing wire for product remains elimination and strong hermetic seals

- Cut-off seal
- 1 x 3.5 mm convex sealing wire and
- 1 x 1.1 mm round cut-off wire for hygienic and attractive product presentation.

OPERATIONAL CONTROL FUNCTIONS

• Time control

Command in seconds for vacuum and seal.

SUPPORT CONTROL FUNCTIONS

- STOP button for partial/full cycle interruption
- Digital maintenance program for pump
- Automatic reminder for oil replacement
- Service detection device

OPTIONAL FUNCTIONS / ACCESSORIES

- Inclined plate for efficient packing of liquid products
- Connection for external vacuuming food containers
- Service kit for standard maintenance
- Trolley with shelves and castors

Option Standard













